System SF30

SUNFLEX

☐ Inquiry ☐ Order

Customer number: _____

Company stamp / address:

Contact person: _____

Telephone: _____

Quotation No.: _____

Commission: _____

Number of systems: _____

Opening direction: ☐ inwards folding ☐ outwards folding (Note: Use interior view!)

Dimensions: Width: _____ (Total unfolding) Height: _____ (incl. possible floor recession)

Number of panel _____ to the left _____ to the right

Colour: ☐ RAL _____ ☐ E6-EV1 ☐ DB703 ☐ DB703 FS ☐ Special colour:_____ ☐ Pre anodizing

Glazing: ☐ 10 mm tempered glass, clear with Heat-Soak-Test ☐ 12 mm tempered glass, clear with Heat-Soak-Test ☐ Special glass: _____

Wall connection left and right:

☐ with rubber gasket



☐ with brush gasket



☐ flush



☐ in EV1 (standard)
☐ in RAL _____

Bottom track: ☐ standard ☐ embed





☐ in EV1 (standard)
☐ in RAL _____
only possible after agreement

Operation/Handle: ☐ inside ☐ inside and outside

☐ Turning knob (Standard) ☐ Mortise latch lock: ☐ with half profile cylinder ☐ with full profile cylinder

☐ Special colour_____ Gap gaskets: ☐ 1 pc per panel joint

☐ Latch: ☐ with PZ ☐ without PZ

☐ Flush handle with shoot-bolt lock ☐ with half profile cylinder ☐ with PZ inside + outside

☐ Flush handle with shoot-bolt lock inside + outside ☐ with half profile cylinder ☐ with PZ inside + outside

Handle height: H = _____ (Indicate handle height from lower panel edge)

Please enclose floor plan resp. view sketch and remarks (please use inside view)

Fax or E-mail to: +49 (0) 2762 / 9253-280 / info@sunflex.de