

☐ Inquiry ☐ Order	Customer number:
Company stamp / address:	Contact person:
	Telephone:
	Quotation No.:
	Commission:
Number of systems:	
Opening direction: inwards folding outwards folding	(Note: Use interior view!)
Dimensions: Width: (Total unfolding)	Height: (incl. possible floor recession)
Number of panel to the left to the right	
Colour:         RAL         E6-EV1         DB703	DB703 FS Special colour: Pre anodizing
Glazing: 10 mm tempered glass, 22 mm tempered clear with Heat-Soak-Test 23 clear with Heat-Soak-Test 24 clear with Heat-Soak-Test 25 clear with Heat-Soak-Test 26 clear with Heat-Soak-Test 27	
Wall connection left and right:	
with rubber gasket with brush gasket	flush
in EV1 (standard) in RAL	
Bottom track: standard embed	
	in EV1 (standard) in RAL only possible after agreement
Operation/Handle: inside inside and outside	
Turning knob (Standard) Mortise latch lock:	with half profile cylinder  with full profile cylinder
Special colour Gap gaskets: 1 pc per panel joint	
Latch: with PZ without PZ	
Flush handle with shoot-bolt lock with half profile cylinder with PZ inside + outside	
Flush handle with shoot-bolt lock inside + outside with half profile cylinder with PZ inside + outside	
Handle height: H = (Indicate handle height from lower panel edge)	

Please enclose floor plan resp. view sketch and remarks (please use inside view)